

Product Specifications		
Model name	75T60P	86T60P
<b>Display</b>		
Size	75"	86"
Screen Type	VA	VA
OC Vender	CSOT	CSOT
Optical Distance	OD20	OD20
Aspect Ratio	16:9	16:9
Resolution	3840(H)x2160(V)	3840(H)x2160(V)
Back Light Unit	DLED	DLED
Response Time (typ.)	8ms	8ms
Refreshing Frequency	60Hz	60Hz
Display Color	1.07B(10bit)	1.07B(10bit)
NTSC%	75%	75%
Brightness with Glass (typ)	400 cd/m2	400 cd/m2
Brightness with Glass (min)	350 cd/m2	350 cd/m2
Contrast Ratio (fvn)	4000:1	4000:1
Viewing Angle	178°	178°
OC Haze%	25%	25%
Life Time	50000 Hours	50000 Hours
Pen holder	Yes	Yes
Front keypad	Power(VOL+ VOL- MENU HOME RETURN Support:Anti-bacterial	Power(VOL+ VOL- MENU HOME RETURN Support:Anti-bacterial
Portrait / Landscape	Landscape	Landscape
18/7 used (need provide proof doc. and ref)	Yes	Yes
<b>Video/Audio</b>		
Speaker Type	Built-in Speaker	Built-in Speaker
Output Power	2*15W speaker 20W subwoofer (Optional)	2*15W speaker 20W subwoofer(Optional)
Mic array	8 Array, Pickup Distance: 0-8M	8 Array, Pickup Distance: 0-8M
Camera	18Million pixels	18Million pixels
<b>Display Connectors</b>		
<b>Front</b>		
HDMI IN 2.0	1	1
USB3.0	2, Public	2, Public
TYPE-C (15W)	1 (15W)	1 (15W)
USB Touch	1	1
<b>Rear</b>		
HDMI IN 2.0	2	2
DP IN 1.2	1	1
VGA	1	1
USB 2.0	1	1
USB 3.0	1	1
SPDIF	1	1
RS232	1	1
LAN(RJ45)	2 (10/100M)	2 (10/100M)
USB Touch	1	1
LINE OUT	1	1
Network	10/100Mbps	10/100Mbps
OPS	1.80PIN	1.80PIN
<b>Touch System</b>		
Sensing Type	IR	IR
System	Windows 7/8/10/WindowsXP/Linux/Mac/Android	Windows 7/8/10/WindowsXP/Linux/Mac/Android
Touch Point	10 points touch windows 20 points Android	10 points touch windows 20 points Android
Touch Tool	Finger, Passive pen, Opaque objects	Finger, Passive pen, Opaque objects
Writing Point	5Points	5points
Response Time	<3.3ms	<3.3ms
Accuracy	±1.5mm(90% area)	±1.5mm(90% area)
Writing height	3.5mm(90% area)	3.5mm(90% area)
Writing double colors with double pens simultaneously	Yes	Yes
minimum object size	3mm	3mm
Surface Hardness	Toughened Glass with Level 7 of Mohs Standard, 7H pencil	Toughened Glass with Level 7 of Mohs Standard, 7H pencil
Glass	High Haze (8%), AG, AF Optional Anti-bacterial	High Haze (8%), AG, AF Optional Anti-bacterial
Air gap	Zero Bonding (1.2mm)	Zero Bonding (1.2mm)
<b>Android System</b>		
System Version	Android 11	Android 11
CPU	A55*4	A55*4
Chipset vender	MTK9666	MTK9666
GPU	G52 2EE MC1@550MHz	G52 2EE MC1@550MHz
RAM	4G	4G
ROM	32G	32G
Wifi dongle	wifi 5 dongle	wifi 5 dongle
Launcher resolution	3840 x 2160	3840 x 2160
Max. input resolution	4K60Hz	4K60Hz
UI	4K20Hz	4K20Hz
<b>Power</b>		
Power Requirements	100-240V~ 50/60Hz	100-240V~ 50/60Hz
Standby Power	≤0.5W	≤0.5W
Normal Mode Power	360W	480W
Overall Power (max. power)	410W	530W
Wake on LAN	Yes	Yes
LAN standby	Yes	Yes
<b>Physical Specifications</b>		
Dimension L*H*W	1707.2*1026.4*88.4mm	1953.4*1165.1*88.4mm
Dimension(backpack) L*W*H	1830*205*1050mm	2075*205*1300mm
Net Weight	51.66KG	66.36KG
Gross Weight	65.4KG	81.71KG
Thickness of machine and wall mount	123.4mm	123.4mm
Thickness of machine itself	88.4mm	88.4mm
VESA	600x400mm	800x400mm
Bezel Size (top/left/right)	28.7/15/15mm	28.7/15/15mm
Bezel Size (Bottom)	39.9mm	39.9mm
<b>Accessories</b>		
AC Power Cable	3 M*1	3 M*1
USB Cable (touch)	(Optional)	(Optional)
HDMI Cable	(Optional)	(Optional)
USB C cable	(Optional)	(Optional)
Writing Pen	2 Pcs, (Support: Anti-bacterial)	2 Pcs, (Support: Anti-bacterial)
Remote Control	1pcs (RC180)	1pcs (RC180)
Battery	1	1
Wall mount	1	1
Stand	Optional	Optional
<b>Environmental Conditions</b>		
Operation Temperature	0°C - 40°C	0°C - 40°C
Operation Humidity	10% - 90%	10% - 90%
Storage Temperature	-20°C - 60°C	-20°C - 60°C
Storage Humidity	10% - 90%	10% - 90%